


NYLON-INSULATED RING TERMINAL DISCRIPTION



PRODUCT INTRODUCTION

Material : Copper
Insulated sleeve : Nylon
Coating : Tin

TERMINAL DISCRIPTION



SR.NO	ITEM NO.		TERMINAL TYPE	DIMENSIONS inc (mm)				STANDARD PACKAGING		STUD SIZE	WIRE RANGE (A.W.G mm ²)
	BRAZED SEAM	BUTTED SEAM		B	d2	L	t	BOX	CARTON		
1	AER1.25-4MB	AER1.25-4M	NYLON-INSULATED RING TERMINALS	0.260 (6.60)	0.169 (4.30)	0.803 (20.40)	0.030 (0.75)	3,000	18,000	#8	22 - 16 A.W.G 0.5 - 1.5 mm ²
2	AER1.25-5B	AER1.25-5		0.315 (8.00)	0.209 (5.30)	0.854 (21.70)				#10	
3	AER2-4B	AER2-4		0.335 (8.50)	0.169 (4.30)	0.906 (23.00)	0.031 (0.80)	2,000	12,000	#8	16 - 14 A.W.G 1.5 - 2.5 mm ²
4	AER2-4MB	AER2-4M		0.260 (6.60)	0.169 (4.30)	0.819 (20.80)				#10	
5	AER2-5B	AER2-5		0.347 (9.50)	0.209 (5.30)	0.906 (23.00)			18,000	#10	
6	AER2-6B	AER2-6		0.472 (12.00)	0.252 (6.40)	1.106 (28.10)			12,000	1/4	
7	AER5.5-4B	AER5.5-4		0.347 (9.50)	0.169 (4.30)	1.051 (26.70)	0.039 (1.00)	1,000	6,000	#8	12 - 10 A.W.G 4 - 6 mm ²
8	AER5.5-4SB	AER5.5-4S		0.291 (7.40)	0.169 (4.30)	1.024 (26.00)				#10	
9	AER5.5-5B	AER5.5-5		0.347 (9.50)	0.209 (5.30)	1.051 (26.70)				1/4	
10	AER5.5-6B	AER5.5-6		0.472 (12.00)	0.252 (6.40)	1.287 (32.70)					